ALL-YEAR CATERING MARQUEE
8m × 13m × 2,5m/3,96m

Construction
WINTER ❄

Roof cover
PVC ab. 580 g/m^2 MS

Side cover
PVC ab. 500 g/m^2 SD

Masking stripes
White

Entry no. 1 - Curtain entrance
ab. Wight 3,83m x Height 3,09m

Entry no. 2 - Curtain entrance
ab. Wight 3,83m x Height 3,09m

Technical data

Size and weight

Width:	8m
Lenght:	13m
Sections:	2m
Height of the side wall:	2,5m
Height of the peak:	3,96m
Area:	104m2
Volume:	283,71m^3

Tarpaulin

Roof tarpaulin:	ab. 580 g/m^2
Side tarpaulin:	ab. 500 g/m^2
Air-Control System:	YES
Hermetic System:	YES
Floor Skirt:	YES
Multi-Size System:	YES
Entry no. 1 - Curtain entrance:	ab. Wight 3,83m x Height3,09m
Entry no. 2 - Curtain entrance:	ab. Wight 3,83m x Height3,09m

Construction

Tube diameter:	ab. 50mm
Connector diameter:	ab. 54mm
Tent feet:	ab. 14cm
Additional construction:	YES
Easy Up & Down System:	YES

Total amount of packets: 28 Combined weight: 500.30kg

Year-round construction: WINTER

Main construction is based on steel tubes ab. Ø 50mm and connectors ab. Ø 54mm. galvanized construction.Through and through screws guarantee reliable connection. The Easy Up & Down System allows a quick change of the tent's height.

Additionally, the tent has:

- Enlarged feet Ø 14cm
- Entrance reinforcements on each side
- Reinforced roof and floor construction

Features of the construction

Easy height adjustment

Easy Up & Down system

The modular construction of "P50" system allows you to increase or decrease the height of the tent at ease. To raise the tent you should buy 0.5m or 1m extension modules . The maximum height of the side of the tent is 4m.

Stronger construction

Additional reinforcements of the entries

By eliminating lower pipes at the entrances, the tent has become even much more practical. Two thick pipes were added on each entrance so that the tent has become stronger. These pipes stiffen the entrances and prevent canvas cover at the entrance from damage.

Yearlong use

The roof and floor construction

Additional construction consists of a lower frame, the upper reinforcements and horizontal and vertical braces of the roof. This solution provides greater load capacity and rigidity of the structure. It also allows the use of a tent during unfavourable weather conditions.

Reliability

The new way of connecting elements

In peak connectors, welded parts have been replaced by horizontal ab. fi 25 mm pipes, which have considerably increased the reliability of the construction. In the new model, the horizontal pipe has been attached to the lower part of the connector to provide greater rigidity of the structure.

Long lasting construction

Thick pipes fi 50 mm

Thick, steel pipes with a fi diameter of ab. 50mm are protected against corrosion by galvanizing. Tent connectors have fi diameter of ab. 54 mm.

Exceptional stability

Enlarged feet 14 cm diameter.

Standard feet of fi 9 cm have been increased by 55%. The new fi 14 cm rate increases stability of the tent and simplifies its assembly.



Reliable connecting elements

The screws passing through

We use the most accurate method of connecting pipes with screws passing through in our tents. This is the only reliable way of connecting elements. In addition, the legs lifting the structure are connected using double screws.

⚠ Tents with snaps or with the screws that do NOT pass through, do not provide safe and permanent installation!

Durable tarpaulin: PVC ab. 580 g/m^2 MS

We only use durable PVC material, similar to the one used on the lorries. The tarpaulin is as thick as ab. 580g/m2, it is UV and heat resistant (between -40 to +60 degrees Celsius). It is also 100% waterproof. The marquee is equipped with AIR CONTROL system which prevents water condensation on the inside of the marquee. Additionally, the marquee was equipped with HERMETIC system, the velcros which tightens the connections and seals it. Side walls are equipped with retention apron. MULTI-SIZE system allows you to change the lenght of the marquee (by assembling additional section which is sold separately).

Features of the tarpaulin



Easy length change
Multi-size roof system

Thanks to Multi-size system, you can easily change the length of the tent. It can be extended by inserting an additional extension set or shortened by eliminating a given segment. Extension sets are 1m or 2m long.

Greater tightness and durability
Hermetic system

The additional Velcro secures the heat inside the tent and provides aesthetic look of it. They make the walls perfectly fit together, forming a coherent whole. Moreover, it prevents dust, rain and snow from entering the tent.



Increases safety
Retention cloak

The increased width of the retention cloak increases the efficiency of water discharge. This ensures that the inner part of the tent stays dry during the rain.

Prevents from water condensation
Air Control System

Double ventilators with shutters placed on both sides of the roof allow proper air flow inside the tent. They prevent the creation of sauna effect and water condensation.

⚠ Only the tent with the upper ventilators on both sides ensure a proper air flow.

Attractive appearance
Leaded windows

The side wall is made of thick PVC ab. 500 g/m2 canvas cover and a large leaded windows. The basic wall is 2m high. Its unique design allows to add 1m or 0.5m to the side wall easily. With the windows placed on each two-meter segment, the tent looks aesthetically. It will be perfect as a trade, exhibition or a party tent.

Additional reinforcement of entrances
Zippers with Velcro

Fastened Velcro strengthened entrances and improved their appearance. Thanks to them, zippers have additional protection against gusty wind. Velcro also make the canvas cover tightened.

Stronger and more practical
the Overlap system

Side canvas is mounted on the tab. This is made to strengthen the entire plating.Thanks to Overlap system, when one element is broken, you do not need



Easy opening
Gates curtain type 2 in 1

Two gate are placed on both side of the tent. Each gate has two independent wings with zipper that can be put

one element is broken, you do not need to replace the entire canvas, all you need is to buy the damaged segment.

sideways or rolled up. The entrance is made of PVC ab. 500 g/m2 canvas cover. Gate is be mounted on special rubber bands with the ball, it makes it easy and fast to disassemble and get the full width and height of the entrance of the tent.

Additional paid features

Increased durability

Additional side cantilevers

On all side walls, additional, lateral, upper and lower cantilevers can be used. Thanks to them, the tent is protected against stronger gusts of wind.

Attractive appearance

Leaded window

The sidewall is made of thick PVC ab. 500 g/m2 canvas cover and a large leaded windows. The basic wall is 2m high. Thanks to its unique design, there is an option to add 1m or 0.5m to the side wall easily. With the windows placed on each two-meter segment, the tent looks aesthetically. It will be perfect as a trade, exhibition or a party tent.

Increased resistance to snow

Additional roof cantilevers

The structure of the roof can be equipped with additional corner cantilevers, which help the main structure to hold the weight of snow.

Easy to use

Sliding gate

The gate is made of rigid construction and PVC ab. 500 g/m2 canvas cover. It consists of two independent wings that can be slid sideways. Thanks to it the entrance is solid and more convenient to use.