

REINFORCED WEDDING MARQUEE
5m x 6m x 2m/2,91m



Construction
SUMMER PLUS 🍁

Roof cover
PVC ab. 560 g/m² SD

Side cover
PVC ab. 500 g/m² SD

Masking stripes
● Blue

Entry no. 1 - Curtain entrance
ab. Wight 2,33m x Height 2,31m

Entry no. 2 - Curtain entrance
ab. Wight 2,33m x Height 2,31m

Technical data

Size and weight

Width: 5m
Lenght: 6m
Sections: 2m
Height of the side wall: 2m
Height of the peak: 2,91m
Area: 30m²
Volume: 73,65m³

Tarpaulin

Roof tarpaulin: ab. 560 g/m²
Side tarpaulin: ab. 500 g/m²
Air-Control System: YES
Hermetic System: YES
Floor Skirt: YES
Multi-Size System: NO

Construction

Tube diameter: ab. 38mm
Tube thickness: ab. 1,2mm
Connector diameter: ab. 42mm
Connector thickness: ab. 1,3mm
Tent feet: ab. 9cm
Additional construction: YES

Entry no. 1 - Curtain entrance: ab. Wight 2,33m x Height 2,31m
Entry no. 2 - Curtain entrance: ab. Wight 2,33m x Height 2,31m

Total amount of packets: 9

Combined weight: 133.95kg

Durable construction: **SUMMER PLUS**





Main construction is based on steel tubes ab. Ø 38mm and connectors ab. Ø 42mm. galvanized construction. Through and through screws guarantee reliable connection.

Additionally, the tent has:

- Big feet fi 9cm
- Reinforcements of the entrances on each side
- Reinforced roof and floor constructions

Features of the construction



Increased durability Roof and floor construction

The additional structure consists of a lower frame and upper reinforcements. This solution provides greater load-bearing capacity and structure stiffness.




Reliability The new way of connecting elements

In peak connectors, welded parts have been replaced by horizontal ab. fi 25 mm pipes, which have considerably increased the reliability of the construction. In the new model, the horizontal pipe has been attached to the lower part of the connector to provide greater rigidity of the structure.



Many years of operation Strong galvanized pipes

We use steel of the highest quality, additionally protected against corrosion by galvanizing, which increases the strength of construction elements and provides long-term operation. Bearing pipes have a fi diameter of ab. 38 mm, while the connectors are enlarged to ab. fi 42 mm.



Reliable connecting of elements

The screws passing through

We use the most reliable method of connecting the pipes with bolts passing through in our tents. This is the only reliable way of connecting elements.



Stable construction Strong feet 9 cm diameter.

In the lower part of the structure, stable feet with fi diameter of 9 cm have been mounted. Thanks to them, anchoring the tent is much more stable, regardless of the type of ground. The feet are hot-dip galvanized, which increases their durability and assures a long-term use.

⚠ Tents with snaps or with bolts screwed in and NOT passing through, do not provide safe and permanent installation!

Durable tarpaulin: PVC ab. 560 g/m² SD



We only use durable PVC material, similar to the one used on the lorries. The tarpaulin is as thick as ab. 560g/m², it is UV and heat resistant (between -40 to +60 degrees Celsius). It is also 100% waterproof. The marquee is equipped with AIR CONTROL system which prevents water condensation on the inside of the marquee. Additionally, the marquee was equipped with HERMETIC system, the velcros which tightens the connections and seals it. Side walls are equipped with retention apron.

Features of the tarpaulin



Modern way of combining tents

You can combine tents as you like


The tents can be joined together with the special gutter.



Greater tightness and durability

Hermetic system

The additional Velcro secures the heat inside the tent and provides aesthetic look of it. They make the walls perfectly fit together, forming a coherent whole. Moreover, it prevents dust, rain and snow from entering the tent.



Increases safety

Retention cloak

The increased width of the retention cloak increases the efficiency of water discharge. This ensures that the inner part of the tent stays dry during the rain.



Adjust the tent to your needs

Any combination of the walls


You can order individual parts of cover in various forms, such as a wall with windows or full walls. Personalize a tent and adjust them to your individual needs.



Prevents from water condensation

Air Control System

Double ventilators with shutters placed on both sides of the roof allow proper air flow inside the tent. They prevent the creation of sauna effect and water condensation.

 Only the tent with the upper ventilators on both sides ensure a proper air flow.



Attractive appearance

Leaded windows


The side wall is made of thick PVC ab. 500 g/m² canvas cover and a large leaded windows. The basic wall is 2m high. Its unique design allows to add 1m or 0.5m to the side wall easily. With the windows placed on each two-meter segment, the tent looks aesthetically. It will be perfect as a trade, exhibition or a party tent.



Change colours

Colour Mix system

The tent is equipped with masking panels, mounted on Velcro. They are available in different colours. This allows you to quickly and easily change the colour of the tent. Just buy the masking



Easy opening

Gates curtain type 2 in 1

Two gate are placed on both side of the tent. Each gate has two independent wings with zipper that can be put sideways or rolled up. The entrance is made of PVC ab. 500 g/m² canvas

panels in the right colour.

cover. Gate is be mounted on special rubber bands with the ball, it makes it easy and fast to disassemble and get the full width and height of the entrance of the tent.

Additional paid features



Lifting set

Expand your space


You can buy a special set to lift the side walls. You can lift one or more walls, in order to gain more space.



Attractive appearance

Leaded window

The sidewall is made of thick PVC ab. 500 g/m² canvas cover and a large leaded windows. The basic wall is 2m high. Thanks to its unique design, there is an option to add 1m or 0.5m to the side wall easily. With the windows placed on each two-meter segment, the tent looks aesthetically. It will be perfect as a trade, exhibition or a party tent.



Easy change of length

Multi-size roof type

Thanks to Multi-size system, you can change the length of the tent easily. It can be extended, by buying a set of extensions or shortened by eliminating a segment. The set extends tent by 1m or 2m.



Maximum illumination for the interior

Transparent roof

It is the most effective way to provide the tent with maximum amount of daylight. This is a great solution when work inside the tent is necessary.